



DNV SILVER/CIMS Tank Container Periodic Inspection Report

Control Number
Date 29-May-24



This certifies that the undernoted tank container has been reinspected in accordance with the regulations indicated.
This inspection is performed subject to 1) DNV's Standard Terms and Conditions and 2) ADR Delegation: NL/ILT/EIGS/025a.

Scope: 2½ Year Inspection 5 Year Inspection

Place of inspection: Moerdijk Tankcontainer Repair, Moerdijk, The Netherlands	Owner's Serial Number DADU 261039-4
Operator/Lessor: Tank Trailer Nederland BV	
Manufacturer: JJAP TANK	Manufacturer's Serial No. 2001206

Applicable Regulations. Enter initial approval No. as applicable

- CSC** GB-LR 64898 08/18 **UK-DOT**
- IMDG** UN PORTABLE T11 **US-DOT** IA-8102
- RID/ADR** NL/LR 64898 // L4BN **AAR 600**
- BAM**
- TIR** GB/C 64898 LR/2018 **TC Impact**
- UIC** IRS 50592 **FRA**

Tank Information	
Year of Manufacture:	2020
Max Gross Weight (Kg):	39000
Tare Weight (Kg):	3780
Capacity (L):	26010
Design Temp (C):	-40/+130
M.A.W.P. (Bar):	4.0
Test Pressure (Bar):	6.0
Top Discharge:	No
Bottom Discharge:	Yes
No. of closures in series:	Three
Shell Material:	SANS 50028-7 : 1.4402
Shell Thickness (mm):	6.0 EMS
Heads Material:	SANS 50028-7 : 1.4402
Heads Thickness (mm):	6.0 EMS
ISO Type:	22K2



Inspection Dates (mm/yy)		
Initial Hydro Test:	06/20	Witness: LR
Last Hydro Test:	06/20	Witness: LR
This Inspection:	29/05/24	
Date Next Inspection Due:	11/26	

Inspections Performed	N/A	In Order	See Comm
Internal Inspection		X	
External Inspection		X	
Hydro Test: 28-May-24 Pressure (Bar): 6		X	
Post Hydro Leakproof Test		X	
Fittings Inspection		X	
Frame Inspection		X	
Decals Inspection		X	
Steam Coils Test Pressure (Bar): 6		X	

Pressure Relief Valves	1st	2nd
Manufacturer/Type:	Fort Vale	N/A
Serial Number:	19087724	N/A
Full Flow Rate (CMHR):	5.768 NM3/S	N/A
Operating Pressure (Bar):	4.40	N/A
Vacuum Setting (Hg):	6.2"	N/A
Bursting Disc (Bar):	N/A	N/A

Surveyors Name:
D. Geerling

Comments:



 Anthony Bova

CSC 11/26
Plate Marking/Stamping: NV or VL 05/24 P IA-9101